CW ♥ Defence

CAMOUFLAGE SOLAR PANEL





- **♥** | CWD270-60P-FGREEN **♥** | CWD270-60P-MBLUE
- **♥** CWD270-60P-MG0LD



High Conversion Efficiency

High panel efficiency to guarantee high power output



Self-Cleaning And Anti-Reflection Glass





Outstanding Low Irradiation Glass

Outstanding panel performance even in weak light conditions



Excellent Durability


Wind load up to 2400 Pa, Snow load up to 5400 Pa



 $0 \sim +5W$ Positive Power Tolerance



Easy Installation




















ELECTRICAL CHARACTERISTICS

| Peak Power (Pmax) | 270Wp |
|-------------------------------|-------------|
| Module Efficiency | 16.07 |
| Maximum Power Voltage (Vmp) | 32.24 |
| Maximum Power Current (Imp) | 8.40 |
| Open Circuit Voltage (Voc) | 37.68 |
| Short Circuit Current (Isc) | 8.88 |
| Power Tolerance [W] | 0~+5 |
| Maximum System Voltage [V DC] | 1500 |
| Operating Temperature | -40 ~ +85°C |
| Fire Safety Class | С |
| Maximum Series Fuse Rating | 20A |

| MECHANICAL SPECIFICATIONS | | | | |
|---------------------------|--------------|--|--|--|
| Cell Dimensions [mm] | 157 x 157 | | | |
| Cells per Module [Pcs] | 60 (6x10) | | | |
| Weight [kg] | 19 | | | |
| Panel Dimensions [mm] | 1668x1007x35 | | | |
| Max. Wind/Snow Load (Pa) | 2400/5400 | | | |
| Junction Box | IP67 / IP68 | | | |




TEMPERATURE CHARACTERISTICS

| Sıcaklık Katsayısı (İsc) | 0.05%/°C |
|---------------------------|-----------|
| Sıcaklık Katsayısı (Voc) | -0.33%/°C |
| Sıcaklık Katsayısı (Pmax) | -0.38%/°C |

PACKING CONFIGURATION

| Container | 20' GP | 40' GP |
|----------------------|--------|--------|
| Pieces per Pallet | 31 | 31 |
| Pieces Per Container | 372 | 868 |
| Pallet Per Container | 12 | 28 |

ELECTRICAL CHARACTERISTICS



^{*} The specifications are obtained under the standard test conditions: 1000W/m2 solar irradiance, 1.5 Air Mass and cell temperature of 25°C. Measurement uncertainty for all panels is 3 %. The actual transactions will be subject to the contracts. These parameters are for reference only and it is not a part of the contracts. The technical specifications in this document may vary. For more information, refer to the "Installation Manual".

Ver.2310.02

^{*} CW DEFENCE products are project based products. Changes can be made upon your needs.

^{*} CW DEFENCE products are project-based products and can realize special projects upon your requests.